In re Application of:

Foster et al.

Application No.: 10/552,390

Filed: May 30, 2006

Page 2

Amendments to the Claims:

Please amend claims 1 and 31.

Please cancel claim 27 without prejudice or disclaimer.

This listing of claims will replace all prior versions, and listings, of claims in the

PATENT

Atty Docket No.: MAP1130

application.

Listing of Claims:

1. (Currently Amended) An apparatus for dissolving or suspending a substance in a solvent

comprising:

an outer chamber for containing a dense gas, wherein the outer chamber is an autoclave;

an inlet for supplying the dense gas as a solvent, wherein the inlet is configured such that

the dense gas is introduced through a straight shaft and delivered to the center of the apparatus;

a porous chamber within the outer chamber for containing a substance for dissolution or

suspension with the solvent, the porous chamber having a wall which allows passage of solvent

and the substance dissolved or suspended in the solvent[[,]]; and

an outlet for removing solvent and solution and/or dispersion from the outer

chamber and a turbulence means for creating turbulence within the porous chamber, wherein the

turbulence creating means comprises a drive means to rotate the porous chamber within the outer

chamber.

2. (Original) The apparatus of claim 1, wherein the inlet in the outer chamber supplies

solvent directly to a mouth communicating with the porous chamber.

WEST\223668328.1 368008-000002 In re Application of:

Foster et al.

Application No.: 10/552,390

Filed: May 30, 2006

Page 3

3. (Original) The apparatus of claim 1, wherein the inlet is in the wall of the outer chamber

PATENT

Atty Docket No.: MAP1130

providing dense gas to the region between the porous chamber and the outer chamber.

4. (Original) The apparatus of claim 1, wherein the inlet supplies solvent to the porous

chamber and the region between the porous chamber and the outer chamber.

5. (Original) The apparatus of claim 2, wherein the porous chamber is further provided

with a longitudinally extending shaft communicating with the solvent inlet of the porous

chamber.

6. (Original) The apparatus of claim 5, wherein the shaft is porous or perforated.

7. (Previously Presented) The apparatus of claim 5, wherein the porous chamber is adapted

to receive the substance in the region around the longitudinally extending shaft and the porous

chamber is adapted to receive solvent through the shaft.

Claims 8-9. (Canceled)

10. (Previously Presented) The apparatus of claim 1, wherein the turbulence creating means

further comprises baffles extending from the inner surface of the outer chamber in the region

between the porous chamber and the wall of the outer chamber.

11. (Original) The apparatus of claim 1, wherein the porous chamber is provided with a plug

to hold the substance against the base of the inner chamber.

12. (Original) The apparatus of claim 11, wherein the plug is a planar element abutting the

sides of the inner chamber and is held against the substance by a resilient biasing means.

Claims 13-25. (Canceled)

WEST\223668328.1 368008-000002 In re Application of:

Foster et al.

Application No.: 10/552,390

Filed: May 30, 2006

Page 4

26. (Original) A method of treatment of the subject comprising the steps of administering to

PATENT

Atty Docket No.: MAP1130

the subject an affective amount of particles of a biologically active substance produced using the

apparatus of claim 1.

27. - 28. (Canceled)

29. (Previously Presented) The apparatus of claim 1, wherein the autoclave is adapted to

provide a temperature of between 5°C and 45°C.

30. (Previously Presented) The apparatus of claim 1, wherein the autoclave is adapted to

provide a pressure between about 5 to 200 bar.

31. (Currently Amended) An apparatus for dissolving or suspending a substance in a solvent

comprising:

an outer chamber for containing a dense gas, wherein the outer chamber is an autoclave;

an inlet for supplying dense gas as a solvent, wherein the inlet is configured such that the

dense gas is introduced through a straight shaft and delivered to the center of the apparatus;

a porous chamber within the outer chamber for containing a substance for dissolution or

suspension with the solvent, the porous chamber comprising a wall allowing passage of solvent

and the substance dissolved or suspended in the solvent, and a longitudinally extending shaft in

fluid communication with the inlet, wherein the shaft is porous along the length of the shaft; and

an outlet for removing solvent and solution and/or dispersion from the outer chamber and

a turbulence means for creating turbulence within the porous chamber, wherein the turbulence

creating means comprises a drive means to rotate the porous chamber within the outer chamber.

WEST\223668328.1 368008-000002